



# RUGGED AND DEPENDABLE POCKET TESTER

**APPLICATIONS** ● ● ● Easy aquarium control | Pool & Spa Maintenance | Hydroponics Nutrient Check | All Industries



## Features

### Easy Usage

Just dip the sensor into test solution, stir and get a stable reading in about 20 seconds.

### Affordable Cost

The cost is less compared to the liquid test kits on per year usage as multiple testings can be done. The pH and Redox testers can be used for approximately 365 tests

### Energy Saving

The energy-saving feature shuts off the tester when it is idle. To ensure accurate reading at all times, the unit displays a low battery symbol to alert user to change batteries before the accuracy of readings is affected.

### High Durability

All ECO testers are washable as they are water resistant. The testers are shock resistant and can withstand falls up to a height of 1 meter. (except pH Pro)

### Senz pH Pro



- Precise 0.01pH measurement
- Auto-temperature compensation
- Suitable for lab, clinical use

### ECO $\mu$ Siemen



- For use in low concentration liquid
- For reading scale of 10 $\mu$ S
- Suitable for testing drinking water, natural water & boiler concentrate

### pH Pal



- Precise 0.1pH measurement
- Good readability
- Suitable for industrial processors, food & drink industry, school & education

MODEL	Senz pH Pro	
Operating Range	0 to 14	
Display Resolution	0.01 pH	
Accuracy	$\pm 0.05$ pH	
Calibration Points	2 point	
Temperature compensation	Automatic 0-70 C	
Battery Type	4 X 1.5 V Button Cell (Alkaline A76 or Equivalent)	
Battery Life (continuous use)	Approx. 150 Hours	
Auto shut-off	Approx. 15 minutes	Approx. 60 minutes
Weight	Approximately 135gm	
Size (L x W x H)	170 X 32 X 15mm	

MODEL	ECO $\mu$ Siemen	
Operating Range	10 to 1,990	
Display Resolution	10 $\mu$ S	
Accuracy	$\pm 2\%$ full scale	
Calibration Points	Single	
Temperature compensation	Automatic 0 to 50 C	
Battery Type	4 X 1.5 V Button Cell (Alkaline A76 or Equivalent)	
Battery Life (continuous use)	Approx. 150 Hours	
Auto shut-off	Approximately 15 minutes	
Weight	Approximately 120gm	
Size (Lx W x H)	170 X 32 X 15mm	

MODEL	pH Pal	
Operating Range	0 to 14.0pH	
Display Resolution	0.1pH	
Accuracy	$\pm 0.2\%$ full scale	
Calibration Points	One-point at 7.00pH	
Temperature compensation	N/A	
Battery Type	4 X 1.5 V Button Cell (Alkaline A76 or Equivalent)	
Battery Life (continuous use)	300 Hours	
Size (Lx W x H)	147 X 32 X 15mm	
Weight	Approximately 60gm	
Calibration Solution	7010 Buffer Solution	

## EDT Direct Ion Ltd

Unit 5 Waldershare Park Eythorne  
Dover Kent CT 15 5DQ UK.  
Tel : +44 (0) 1304 829960 Fax: +44 (0) 1304 829970  
e-mail: sales@edt.co.uk website: www.edt.co.uk  
Excellence & Innovation in Electrochemistry.

## CONTACT

## Stockist & Distributor

Al-Fanara Scientific Lab. Devs. Tr. Est P.O. Box 24936,  
Sharjah U.A. E  
Tel : 971-6-5324511 Fax : 971-6-5324510

## DISTRIBUTOR

