



Series 4 Portable Combined pH And Conductivity /TDS Meter - QP458

The QP458 Portable combined pH and Conductivity meter is the third in a series of Quality Portable meters from EDT directION. All are state of the art instruments made in the UK.

The clear backlit graphic display guides the user through every operation ensuring that even the most unskilled operation can perform accurate analysis without an instruction manual.

Every instrument in the QP range has a mini USB output for printing or exporting sample and calibration data. If printing is not possible there is a 10,000 data point, 64 file internal memory to enable field data to be recorded.

Power is via 4 x AA batteries. Lifetime is impressive due to a highly efficient display with brightness and contrast options along with many other power saving features.

Other features include:

- Dual pH and Conductivity Display
- 1, 2 or 3 Point pH Calibration
- Auto Conductivity Calibration
- Auto endpoint
- Automatic Temperature Compensation (ATC)
- Automatic Standard Recognition
- pH Buffer correction
- Calibration alarms
- Millivolt and Relative millivolt modes
- Total Dissolved Solids (TDS) Mode
- Data logging and internal Data storage.
- Micro USB Data output
- Real time clock
- BNC /DIN and 3.5mm Jack connectors
- Impressive array of accessories and consumables.

The QP range of products are extremely Tough, Splash-proof and practical and carry a two year warranty.

SPECIFICATION TABLE

Summary	Technical specification: Same as QP451 pH & QP481 Conductivity Meters
Automatic pH Calibration	Automatic calibration in all modes
Battery Life	Over 200 hours continuous use. Power saving features include: Auto off, Backlight control, logging sleep mode.
Conductivity Accuracy	+/- 0.2% of reading
Conductivity Range	Auto-ranging from 0-999mS/cm in appropriate units
Connection	Multi pin DIN for Conductivity/Temperature combined probe. BNC for pH with 3.5mm Jack for ATC
Data Output	Mini USB. Outputs CSV at 38400 Baud
Data Storage	Dynamic internal storage of up to 64 files. Logging maximum 10,000 data points
Display	Backlit LCD graphic display
Power requirement	4 x AA batteries
Range pH	-2 to 16 pH
Reference Temperature	Set at 25 degrees C
Size	175x88x48mm (lwh). Meter only
Warranty	2 Year Warranty. Excludes Electrodes accessories and consumables and Misuse.
Weight	350g (Meter Only)

For more information on this product visit www.edt.co.uk/QP458

Related Products



Series 4 Portable Combined pH and Conductivity Meter Kit



Buffer Solution pH7.00 (Yellow) 500ml



Conductivity Calibration Solution 1413 mS/cm (100ml)

Stay in touch with EDT



Telephone +44 (0)1304 829960
The Old Silo Store, Dover CT7 7DL
www.edt.co.uk

