



Glass Conductivity Cell K=0.1 - E8072

The E8072 Glass Conductivity Cell is for applications where the sample conductivity is low and the standard E8071 general purpose conductivity cell does not have the required sensitivity.

Typical applications could range from checking the quality of de-ionized or distilled water to sensitive analysis of ecological water sources.

The 12mm glass body has two internal active platinum electrodes in close proximity which have to be submerged in the samples to a minimum depth of around 2cm.

The E8072 Conductivity cell is suitable for use with the complete range of EDT conductivity meters and contains a temperature sensor to enable all readings to be temperature compensated (ATC). Calibration solutions are available and the recommendation for general purpose cells (K=1) is to calibrate using a 1413uS/cm standard such as EDT A3052 and A3053.

Temperature reading and compensation range is 0-50 degrees centigrade. For general analysis above 500uS/cm use a K=1 cell (E8071). For process measurements or where the use of glass is not acceptable EDT manufacture a complete range of Conductivity cells to suit most applications.

The E8072 Conductivity cell has a fixed 1 metre cable with a DINconnector to fit EDT meters. We also manufacture conductivity cells compatiblewith most models and make of instrument. Contact usso we can advise the part number and price

To watch a simple calibration please visit our website.

SPECIFICATION TABLE

Body Type	Glass
Cell Type	Platinum Plates
Conductivity Cell Range	0.1 μ S/cm to 2000 μ S/cm
Connector	DIN Connector for EDT Conductivity Meters
Diameter	12mm
Length	155mm

For more information on this product visit www.edt.co.uk/E8072

Related Products



Advanced Portable Conductivity Meter Kit



General Purpose Conductivity Meter



Polymer Conductivity Cell K=1

Stay in touch with EDT



Telephone +44 (0)1304 829960
The Old Silo Store, St. Radigund's Abbey, Dover CT15 5DQ
www.edt.co.uk

